

09-13-00

PTO/SB/05 (2/98)

Approved for use through 09/30/2000. OMB 0651-0032

Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

Please type a plus sign (+) inside this box →



U.S. PTO

UTILITY
PATENT APPLICATION
TRANSMITTAL

Attorney Docket No. 4015-785

First Inventor or Application Identifier

Bloebaum

Title

POSITION DETECTION SYSTEM INTEGRATED INTO
MOBILE TERMINAL

Express Mail Label No.

EL634166589US

(Only for new nonprovisional applications under 37 CFR § 1.53(b))

APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents.

ADDRESS TO:

Assistant Commissioner for Patents
Box Patent Application
Washington, DC 20231

1. ☒ *Fee Transmittal Form (e.g., PTO/SB/17)
(Submit an original and a duplicate for fee processing)
2. ☒ Specification [Total Pages 28]
(preferred arrangement set forth below)
- Descriptive title to the Invention
 - Cross References to Related Applications
 - Statement Regarding Fed sponsored R & D
 - Reference to Microfiche Appendix
 - Background of the Invention
 - Brief Summary of the Invention
 - Brief Description of the Drawings (if filed)
 - Detailed Description
 - Claim(s)
 - Abstract of the Disclosure
- ☒ Drawing(s) (35 U.S.C. 113) [Total Sheets 6]
- ☒ Oath or Declaration [Total Pages 3]
- a. ☒ Newly executed (original or copy)
- b. ☐ Copy from a prior application (37 C.F.R. § 1.63(d))
(for continuation/divisional with Box 17 completed)
[Note Box 5 below]
- i. ☐ DELETION OF INVENTOR(S)
Signed statement attached deleting
inventor(s) named in the prior application,
see 37 C.F.R. §§ 1.63(d)(2) and 1.33(b).
- ☐ Incorporation By Reference (useable if Box 4b is checked)
The entire disclosure of the prior application, from which a
copy of the oath or declaration is supplied under Box 4b,
is considered as being part of the disclosure of the
accompanying application and is hereby incorporated by
reference therein.

6. ☐ Microfiche Computer Program (Appendix)
7. Nucleotide and/or Amino Acid Sequence Submission
(if applicable, all necessary)
- a. ☐ Computer Readable Copy
- b. ☐ Paper Copy (identical to computer copy)
- c. ☐ Statement verifying identity of above copies

ACCOMPANYING APPLICATION PARTS

8. ☒ Assignment Papers (cover sheet & document(s))
9. ☐ 37 C.F.R. § 3.73(b) Statement ☒ Power of Attorney
(when there is an assignee)
10. ☐ English Translation Document (if applicable)
11. ☒ Information Disclosure Statement (IDS)/PTO-1449 ☒ Copies of IDS Citations
12. ☐ Preliminary Amendment
13. ☒ Return Receipt Postcard (MPEP 503)
(Should be specifically itemized)
14. ☐ *Small Entity ☐ Statement filed in prior application,
Statement(s) Status still proper and desired
15. ☐ Certified Copy of Priority Document(s)
(if foreign priority is claimed)
16. ☒ Other: Express Mail Certification

*NOTE FOR ITEMS 1 & 14: IN ORDER TO BE
ENTITLED TO PAY SMALL ENTITY FEES, A SMALL
ENTITY STATEMENT IS REQUIRED (37 C.F.R.
§ 1.27), EXCEPT IF ONE FILED IN A PRIOR
APPLICATION IS RELIED UPON (37 C.F.R. § 1.28).

17. If a CONTINUING APPLICATION, check appropriate box and supply the requisite information below and in a preliminary statement:

- ☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No: _____ / _____
- Prior application information: Examiner: Group/Art Unit:

18. CORRESPONDENCE ADDRESS

☒ Customer Number or Bar Code Labelor ☐ Correspondence address below

(Insert Customer Number or Bar code label here)

NAME				
ADDRESS				
CITY	STATE	ZIP CODE		
COUNTRY	TELEPHONE	FAX		

Name (Print/Type)	Taylor M. Davenport	Registration No. (Attorney/Agent)	42,466
Signature		Date	9/12/00

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Box Patent Application, Washington, DC 20231.

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

FEE TRANSMITTAL

Patent fees are subject to annual revision on October 1

These are the fees effective December 29, 1999.

Small Entity payments must be supported by a small entity statement.
otherwise large entity fees must be paid. See Forms PTO/SB/09-12.

See 37 C.F.R. §§ 1.27 and 1.28.

TOTAL AMOUNT OF PAYMENT \$1162.00

Complete if Known

Application Number	TBA
Filing Date	TBA
First Named Inventor	Bloebaum
Examiner Name	TBA
Group Art Unit	TBA
Attorney Docket No.	4015-785

METHOD OF PAYMENT (check one)

- 1.
- ☒
- The Commission is hereby authorized to charge indicated fees and credit any over payments to:

Deposit
Account
Number

18-1167

Deposit
Account
Name

Coats & Bennett, P.L.L.C.

☒ Charge Any Additional
Fee Required Under
37 CFR §§1.16 and 1.17☐ Charge the Issue Fee Set in
37 CFR §1.18 at the Mailing of the
Notice of Allowance

- 2.
- ☒
- Payment Enclosed:

☒ Check☐

Money Order

☐

Other

FEE CALCULATION**1. BASIC FILING FEE**

Large Fee Code	Entity Fee (\$)	Small Fee Code	Entity Fee (\$)	Fee Description	Fee Paid
101	690	201	345	Utility filing fee	690.00
106	310	206	155	Design filing fee	
107	480	207	240	Plant filing fee	
108	760	208	380	Reissue filing fee	
114	150	214	75	Provisional filing fee	
SUBTOTAL (1)					\$690.00

2. EXTRA CLAIM FEES

Total Claims		Extra Claims		Fee from below		Fee Paid	
31	-20** =	11	X	18	=	198.00	
6	-3** =	3	X	78	=	234.00	
Multiple Dependent Claims			X		=		
** or number previously paid, if greater; For Reissues, see below							
Large Fee Code	Entity Fee (\$)	Small Fee Code	Entity Fee (\$)	Fee Description			
103	18	203	9	Claims in excess of 20			
102	78	202	39	Independent claims in excess of 3			
104	260	204	130	Multiple dependent claim			
109	78	209	39	**Reissue independent claims over original patent			
110	18	210	9	**Reissue claims in excess of 20 and over original patent			
SUBTOTAL (2)						\$432.00	

FEE CALCULATION (continued)**3. ADDITIONAL FEES**

Large Fee Code	Entity Fee (\$)	Small Fee Code	Entity Fee (\$)	Fee Description	Fee Paid
105	130	205	65	Surcharge - late filing fee or oath	
127	50	227	25	Surcharge - late provisional filing fee or cover sheet	
139	130	139	130	Non-English specification	
147	2,520	147	2,520	For filing a request for reexamination	
112	920*	112	920*	Requesting publication of SIR prior to Examiner action	
113	1,840*	113	1,840*	Requesting publication of SIR after Examination action	
115	110	215	55	Extension for reply within first month	
116	380	216	190	Extension for reply within second month	
117	870	217	435	Extension for reply within third month	
118	1,360	218	680	Extension for reply within fourth month	
128	1,850	228	925	Extension for reply within fifth month	
119	300	219	150	Notice of Appeal	
120	300	220	150	Filing a brief in support of an appeal	
121	260	221	130	Request for oral hearing	
138	1,510	138	1,510	Petition to institute a public use proceeding	
140	110	240	55	Petition to revive - unavoidable	
141	1,210	241	605	Petition to revive - unintentional	
142	1,210	242	605	Utility issue fee (or reissue)	
143	430	243	215	Design issue fee	
144	580	244	290	Plant issue fee	
122	130	122	130	Petitions to the Commissioner	
123	50	123	50	Petitions related to provisional applications	
126	240	126	240	Submission of Information Disclosure Stmt.	
581	40	581	40	Recording each patent assignment per property (times number of properties)	40.00
146	760	246	380	Filing a submission after final rejection (37 CFR 1.129(a))	
149	760	249	380	For each additional invention to be examined (37 CFR 1.129(b))	
Other fee (specify)					
Other fee (specify)					
*Reduced by Basic Filing Fee Paid					
SUBTOTAL (3)					\$40.00

SUBMITTED BYTyped or
Printed Name Taylor M. Davenport

Signature

Taylor M. Davenport

Date

9/12/00

Complete (if applicable)

Reg. Number 42,466

Deposit Account
User ID 18-1167

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.

Express Mail Label No.: EL634166589US

Date Mailed: September 12, 2000

UNITED STATES PATENT APPLICATION FOR GRANT OF LETTERS PATENT

SCOTT BLOEBAUM
HAVISH KOORAPATY
INVENTORS

**POSITION DETECTION SYSTEM INTEGRATED INTO
MOBILE TERMINAL**

COATS & BENNETT, P.L.L.C.

P.O. Box 5
Raleigh, NC 27602
(919) 854-1844

POSITION DETECTION SYSTEM INTEGRATED INTO MOBILE TERMINAL

BACKGROUND OF THE INVENTION

5 The present invention is directed to a mobile terminal integrated with a position detection system and a method to minimize traffic on a mobile network.

Mobile terminals such as cellular phones, personal digital assistants, laptops equipped with wireless modems, and the like have exploded into the public consciousness. These devices enable individuals to remain connected to other people without being tied to a land-based phone.

10 Because mobile terminals are in fact, by definition, mobile, many recent patents have discussed incorporating position detection capabilities into the mobile terminals so that the user may know where they are. Alternatively, such technology may be used so that a third party knows where the mobile terminal is located. One such proposed use of a position detection system is to deter theft; items being protected may periodically report their present whereabouts through a wireless modem as determined by the position detection system.

15 One popular position detection system targeted for such incorporation into a mobile terminal is the Global Positioning System (GPS), which relies on a constellation of satellites to assist a GPS receiver in determining its location. Other terrestrial or satellite-based systems do exist, such as GLONASS, the Russian equivalent of GPS. Likewise, position detection systems have been proposed which would use base stations in a mobile network to provide triangulation data for mobile terminals within the mobile network.

20 Unfortunately, while integration of position detection systems and mobile terminals seems like a laudable goal and is technically feasible, such integration may tend to ignore the realities behind such position detection systems and mobile networks.

For example, GPS has an extremely slow data transfer rate. It may take on the order of ten to twenty minutes to secure enough information from the satellites to determine position without any *a priori* knowledge. While GPS may be an extreme example, other positioning systems may experience similar delays. Inability to secure quick position information may lead to consumer frustration. In a theft deterrent usage, the long lag in determining a position of a stolen item may hinder recovery efforts.

Several solutions to this problem have been proposed, although presently without any significant commercial exploitation. In a first solution, "almanac" information is stored in the mobile terminal so that the mobile terminal can determine approximately where in the sky to search for satellite signals from which to determine position. In a second solution, the mobile terminal inquires over the mobile network to a server about the precise present location ("ephemeris") of the satellites.

While these solutions may assist the mobile terminal in determining where to look for satellites from the GPS, they still are not satisfactory. The first solution does not speed up the location determination process that much. Even where a complete set of almanac information is available in the mobile terminal, it may take on the order of a full minute to receive enough information from the GPS satellites to determine the precise location of the mobile terminal. The second solution creates a huge bandwidth demand on the mobile network since the ephemeris information is sent about all the satellites, not merely the ones visible. Such ephemeris could be broadcast to multiple mobile terminals over a shared control channel, or provided in individual responses to requests from mobile terminals. Since the common control channel is typically a scarce resource, clogging it with lots of ephemeris information may preclude another service. While providing ephemeris in individual responses to requests alleviates this problem, it is

relatively inefficient from a network management point of view. Moreover, when the number of mobile terminals requesting ephemeris data increases, the problem of using bandwidth, another scarce resource, is not alleviated.

Thus, there is a need for a system or technique that limits reliance on information from the position detection system, whether that information be provided directly from the position detection assisting devices or from a server that has received that information from the position detection system.

BRIEF SUMMARY OF THE INVENTION

The present invention solves the problems associated with the prior art by hybridizing the solutions of the prior art. An almanac is stored in memory associated with a mobile terminal. This almanac may periodically be updated as needed. The mobile terminal initially inquires of the almanac what position detection assisting devices should be visible to the mobile terminal. The mobile terminal then requests ephemeris for only those position detection assisting devices that are theoretically visible to the mobile terminal. A server in the mobile network then provides the information about only the requested position detection assisting devices. The server need not know where the mobile terminal is located. This conserves bandwidth on the mobile network by reducing the amount of information that need be provided to the mobile terminals and at the same time reduces the time taken to compute the position of the mobile terminal.

In another embodiment, an almanac is stored in memory associated with a mobile terminal. This almanac may periodically be updated as needed. The mobile terminal initially inquires of the almanac what position detection assisting devices should be visible to the mobile

terminal. After determining which position detection assisting devices should be visible, the mobile terminal attempts to receive information from the theoretically visible position detection assisting devices. The mobile terminal culls the actually visible position detection assisting devices from the theoretically visible. The mobile terminal then requests ephemeris for only those position detection assisting devices that are actually visible to the mobile terminal. A server in the mobile network then provides the information about only the requested position detection assisting devices. This provides similar advantages as that listed above and may result in even less bandwidth consumption.

In an alternate embodiment, the mobile terminal evaluates the almanac not only for the position detection assisting devices that may be visible, but also for the timeliness of the information in the almanac. If the information in the almanac is sufficiently timely, perhaps because of a recent update to the almanac about the position of the position detection assisting device, information is not requested for that position detection assisting device, but rather information is only requested for those position detection assisting devices whose information is stale and who should be visible.

In still another embodiment, even if many satellites or position detection assisting devices are visible to the mobile terminal, the mobile terminal may request ephemeris information about only a subset of the position detection assisting devices necessary and sufficient to establish position. Thus, for example, if seven satellites are visible, ephemeris information may be requested about only four.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 illustrates a schematic drawing of a communication system suitable for use with the present invention;

Figure 2 illustrates a schematic drawing of a mobile terminal for use in the communication system of Figure 1;

Figure 3 illustrates a schematic drawing of a communication system wedded to a first position detection system;

Figure 4 illustrates a schematic drawing of a communication system wedded to a second position detection system;

Figure 5 illustrates as a flow chart the methodology of one embodiment of the present invention; and

Figure 6 illustrates as a flow chart the methodology of a second embodiment of the present invention.

DETAILED DESCRIPTION OF THE INVENTION

The present invention is directed to an improvement on communication between mobile terminals and a mobile network wherein the communication is used to facilitate position detection by the mobile terminal. An understanding of an entire communications system and mobile terminal may be helpful for a proper understanding of the context of the present invention. While the following discussion is couched in terms of a TIA/EIA-136 communication system, it should be appreciated that the present invention is equally applicable to Digital Advance Mobile Phone Service (D-AMPS), European Total Access Communication System (ETACS), Code Division Multiple Access (CDMA), Global System for Mobile Communication

(GSM), Pacific Digital Cellular (PDC), and the like, the standards and documentation of which are herein incorporated by reference.

Turning now to Figure 1, a communication system 10 is illustrated. In particular, the communications system 10 includes the Public Switched Telephone Network (PSTN) 20 and the Public Land Mobile Network (PLMN) 30, which may, in turn, be connected to one or more Localized Wireless Telephone Systems (LWTS, only one shown) 60. LWTS 60 may be proprietary or public as needed or desired. While not shown, satellites may be used as needed either within the PSTN 20 or the PLMN 30 to provide remote communication links, such as across oceans or the like.

The operation of the PSTN 20 is well established and subject to extensive documentation beyond the scope of the present invention and therefore a more detailed discussion is omitted.

PLMN 30 may include a plurality of proprietary mobile networks 40, such as those operated by AT&T and BELLSOUTH MOBILITY, also known as service providers. Each mobile network 40 may include a plurality of Mobile Switching Centers (MSCs) 42. Note that in a TIA/EIA-136 system, MSC stands for Mobile Switching Center. Equivalently, in a GSM system, MSC stands for a Mobile Services Switching Center. The acronym and the functions remain identical, however, the term for which the acronym stands is slightly different. Other systems may have yet other names, however, the general function of the MSC as herein described is intended to be embraced. At least one MSC 42 in the PLMN 30, and more likely one MSC 42 in each mobile network 40 is connected via a gateway to the PSTN 20. Some MSCs 42 may also serve as gateways connecting the various mobile networks 40 within the PLMN 30. Gateway functions may be all consolidated at a single MSC 42 within a mobile network 40 or dispersed amongst a plurality of MSCs 42 within a mobile network 40 as needed

or desired. At least one MSC 42 within a particular mobile network 40 may be communicatively connected to a Home Location Register (HLR) 44 and a Visitor Location Register (VLR) 46.

Additionally, each mobile network 40 may be equipped with a message center 48

communicatively connected to an MSC 42. Each MSC 42 may further be communicatively

5 connected to a plurality of base stations 50. An MSC 42 responsible for a LWTS 60 may treat

the LWTS 60 as another base station 50 or a plurality of base stations 50 depending on the

internal structure of the LWTS 60 in question. Each base station 50 may be communicatively

connected to one or more mobile terminals 100, typically over an RF communications channel.

The function of the MSCs 42 is to route calls and signals in the mobile network 40 to the

10 appropriate destination. To perform this function, a mobile network 40 relies on the HLR 44 and

the VLR 46. HLR 44 is used to store information concerning subscribers to a mobile network

40, e.g., AT&T's subscribers. This information typically includes the subscriber's name and

15 address for billing purposes, the serial number of the subscriber's mobile terminal 100, and the

services, which the subscriber is entitled to receive. In addition, the current coarse location of

the subscriber, as evidenced by the current location of their mobile terminal 100, is stored in the

HLR 44. Note that in this context the current coarse location is a very rough location

determination, as in, the mobile terminal 100 is within this cell, which may be anywhere from

300 m to 35 km in diameter.

The current coarse location of the subscriber is secured when the mobile terminal 100 is

20 powered on and at periodic intervals thereafter. In particular, the mobile terminal 100 registers

through the nearest base station 50 with an MSC 42. This is referred to herein as the "serving

MSC." The serving MSC 42 then sends information to the HLR 44 indicating in which cell of

the mobile network 40 the mobile terminal 100 may be found. This assumes that the subscriber is in his home network - i.e., the one in which he has a service contract.

Mobile terminal 100 also registers through the nearest base station 50 and hence with an MSC 42 when it travels between two different service areas (areas served by different MSCs 42).

5 As part of this registration procedure, the mobile terminal 100 transmits its Mobile Identification Number (MIN) to the closest base station 50, which in turn passes the information to the appropriate MSC 42. MSC 42 uses the MIN to determine which HLR 44 to access. When the mobile terminal 100 registers with the new MSC 42, the new servicing MSC 42 updates the HLR 44 with the current coarse location of the mobile terminal 100. When an MSC 42 receives a call addressed to a subscriber that is not currently in that MSC's service area, the MSC 42 will query the HLR 44 for the subscriber's current coarse location so that the call can be forwarded to the MSC 42 currently serving the subscriber.

10 VLR 46 is used to store information about subscribers of mobile terminals 100 that are not in their home network. When subscribers roam outside of their home network, the VLR 46 in the mobile network 40 being visited tracks the subscriber's location and verifies the Mobile Identification Number (MIN) of the mobile terminal 100. The VLR 46 in the network being visited queries the HLR 44 in the subscriber's home service area to authenticate the subscriber and determine the services to which the subscriber is entitled. Information concerning the subscriber is stored in the VLR 46 as long as the subscriber remains registered in the visited network. VLR 46 also stores the current coarse location of the subscriber. The subscriber's current coarse location is communicated back to the home network HLR 44 so that the home mobile network 40 will know where to forward a call addressed to the subscriber who is currently outside the home mobile network 40.

Together, the HLR 44 and the VLR 46 provide the information needed by the MSCs 42 to route calls to the appropriate destination. The routing may further be accomplished by handing the call to another mobile network 40, locating the appropriate base station 50, or passing the call to the PSTN 20 as is appropriate. The exact protocols and communication regimens between the various entities in a mobile network 40 are well documented, such as in TIA/EIA-136, previously incorporated by reference.

Many mobile networks 40 implement a service called short message service (SMS). This service allows subscribers to send and receive short text messages. Messages originating from, or terminating at, a mobile terminal 100 in the network 40 are stored in the message center 48 connected to an MSC 42. Message centers 48 are well understood in the art and a further discussion is omitted.

LWTS 60 may be public or proprietary as needed or desired, and is typically a private network installed in a building or on a campus. LWTS 60 allows employees or other persons working in the building or on the campus to use a mobile terminal 100 as an office telephone. LWTS 60 connects with an MSC 42 in the PLMN 30. Thus, subscribers of the LWTS 60 may move seamlessly between the PLMN 30 and the LWTS 60. LWTS 60 may include a control and radio interface (not shown) and a plurality of transceiver stations.

Turning now to Fig. 2, a mobile terminal 100 typically includes a controller 122, an operator interface 126, a transmitter 138, a receiver 150, and an antenna assembly 158. Operator interface 126 typically includes a display 128, keypad 130, interface control 132, microphone 134, and a speaker 136. Display 128 allows the operator to see dialed digits, call status, and other service information. Keypad 130 allows the operator to dial numbers, enter commands, and select options. Interface control 132 interfaces the display 128 and keypad 130 with the

controller 122. Microphone 134 receives acoustic signals from the user and converts the acoustic signals to an analog electrical signal. Speaker 136 converts analog electrical signals from the receiver 150 to acoustic signals that can be heard by the user.

The analog electrical signal from the microphone 134 is supplied to the transmitter 138.

5 Transmitter 138 includes an analog to digital converter 140, a digital signal processor 142, and a phase modulator and RF amplifier 148. Analog to digital converter 140 changes the analog electrical signal from the microphone 134 into a digital signal. The digital signal is passed to the digital signal processor (DSP) 142, which contains a speech coder 144 and channel coder 146. Speech coder 144 compresses the digital signal and the channel coder 146 inserts error detection, error correction and signaling information. DSP 142 may include, or may work in conjunction with, a DTMF tone generator (not shown). The compressed and encoded signal from the digital signal processor 142 is passed to the phase modulator and RF amplifier 148, which are shown as a combined unit in Figure 2. The modulator converts the signal to a form that is suitable for transmission on an RF carrier. RF amplifier 148 then boosts the output of the modulator for transmission via the antenna assembly 158.

Receiver 150 includes a receiver/amplifier 152, digital signal processor 154, and a digital to analog converter 156. Signals received by the antenna assembly 158 are passed to the receiver/amplifier 152, which shifts the frequency spectrum, and boosts the low-level RF signal to a level appropriate for input to the digital signal processor 154.

20 Digital signal processor 154 typically includes an equalizer to compensate for phase and amplitude distortions in the channel corrupted signal, a demodulator for extracting bit sequences from the received signal, and a detector for determining transmitted bits based on the extracted sequences. A channel decoder detects and corrects channel errors in the received signal. The

channel decoder also includes logic for separating control and signaling data from speech data.

Control and signaling data are passed to the controller 122. Speech data is processed by a speech decoder and passed to the digital to analog converter 156. Digital signal processor 154, may include, or may work in conjunction with, a DTMF tone detector (not shown). Digital to analog
5 converter 156 converts the speech data into an analog signal that is applied to the speaker 136 to generate acoustic signals that can be heard by the user.

Antenna assembly 158 is connected to the RF amplifier of the transmitter 138 and to the receiver/amplifier 152 of the receiver 150. Antenna assembly 158 typically includes a duplexer
10 160 and an antenna 162. Duplexer 160 permits full duplex communications over the antenna 162.

Controller 122 coordinates the operation of the transmitter 138 and the receiver 150, and may for instance take the form of a typical microprocessor. This microprocessor may be a dedicated or shared microprocessor and may be a single processor or multiple parallel processors as needed or desired. This coordination includes power control, channel selection, timing, as
15 well as a host of other functions known in the art. Controller 122 inserts signaling messages into the transmitted signals and extracts signaling messages from the received signals. Controller 122 responds to any base station commands contained in the signaling messages, and implements those commands. When the user enters commands via the keypad 130, the commands are transferred to the controller 122 for action. Memory 124 stores and supplies information at the
20 direction of the controller 122 and preferably includes both volatile and non-volatile portions.

In addition to the above-described elements, the mobile terminal 100 may also include a location detector 164 in communication with the controller 122. Location detector 164 may have its own antenna (not shown) or may share antenna 162. Location detector 164 may be a Global

Positioning System (GPS), an Time Difference Of Arrival (TDOA - where the mobile terminal 100 computes position using observed timing of bursts from multiple base stations 50), a Time of Arrival system (TOA - where the mobile network 40 computes position using mobile terminal 100 bursts observed by multiple base stations 50), or other satellite or terrestrial system as needed or desired. It should be appreciated that while presently TDOA has been characterized as a downlink solution and TOA as an uplink solution, both may be implemented as uplink or downlink solutions as needed or desired. Typically, the location detector 164 will output a geocoordinate expressed as a longitude, latitude, and, optionally, altitude coordinates corresponding to the present location of the mobile terminal 100. In contrast to the coarse location determination made by the mobile network 40, a geocoordinate may, with present civilian systems, be accurate to within approximately five to two hundred meters.

It should be appreciated that the term mobile terminal may include a cellular radiotelephone with or without a multi-line display; a Personal Communications System (PCS) terminal that may combine a cellular radiotelephone with data processing, facsimile and data communications capabilities; a PDA that can include a radiotelephone, pager, Internet/intranet access, Web browser, organizer, and/or calendar; and a conventional laptop and/or palmtop receiver or other appliance that includes a radiotelephone transceiver. Mobile terminals may also be referred to as "pervasive computing" devices. Thus, while the present discussion may be couched in terms of a phone, the present invention is equally applicable to these other sorts of devices. The previous discussion was by way of example, and not intended to be limiting on the definition of a mobile terminal.

With that discussion of mobile networks 40 and mobile terminals 100, it is now possible to discuss using a mobile terminal 100 with a position detection system 200 or 220. Exemplary

position detection systems 200, 220 are shown in Figures 3 and 4. In particular, a satellite based position detection system 200, such as GPS or GLONASS, is illustrated in Figure 3. Satellite based position detection system 200 employs a constellation of satellites 201 (only one shown) that orbit the earth in known trajectories. Applications 210 may be run at a number of positions
5 that require location information from the position detection system 200.

In a first embodiment, an application 210 may run on the mobile terminal 100. An example of such an application would be a simple location program that tells the user of the mobile terminal 100 where the mobile terminal 100 is located. In a second embodiment, an MSC 42 (Fig. 1) within the mobile network 40 may have an application 210 running thereon that solicits information about the whereabouts of a particular mobile terminal 100. This may be for
10 emergency purposes, billing purposes, or some other reason. In a third embodiment, a server 202 external to the mobile network 40 may have an application 210 that inquires as to the whereabouts of a particular mobile terminal 100. Examples of such usages include delivery services inquiring where their drivers are located as evidenced by the location of the drivers' mobile terminals 100. Server 202 interfaces with the mobile network 40 through conventional
15 means and instructs the mobile terminal 100 to report its present location. Note that server 202 may also be in communication with the position detection system 200 and be adapted to receive almanac and ephemeris information therefrom routinely.

An alternate, terrestrial position detection system 220 is illustrated in Figure 4. In particular, a mobile terminal 100 uses TDOA, TOA, or other such methodology to determine its
20 position. Again, applications 210 may be operating at one or more locations and periodically need information about the present location of a particular mobile terminal 100. It should be appreciated that the position detection system may be a hybrid of satellite and terrestrial position

detection assisting devices. The present invention is well suited for all three situations, terrestrial, satellite, and hybrid.

For the purposes of the present invention, the term “position detection assisting devices” is defined as including satellites, such as a GPS satellite 201, base stations 50 in an TDOA or TOA system, and other devices that enable the location detector 164 to determine the present location of the mobile terminal 100.

Regardless of the reason that application 210 wishes to know the location of the mobile terminal 100, the fact remains that an application 210 has made an inquiry as to the location of the mobile terminal 100. In the prior art, in the context of a GPS, the mobile terminal 100 would have to either download from the satellite 201 almanac and/or ephemeris information. This may take approximately twelve and a half minutes. Alternatively in the prior art, the mobile terminal 100 would inquire over the mobile network 40 and retrieve almanac and/or ephemeris information from the mobile network 40 or the server 202. This information would then be broadcast over the mobile network 40, consuming bandwidth and making the jobs of network administrators more difficult. For example, such ephemeris information may be broadcast on the BATS service of the DCCH channel in a TIA/EIA-136 based mobile network 40 and over the CBCH or BCCH in a GSM based mobile network 40. While providing ephemeris in individual responses to requests from different mobile terminals 100 alleviates this problem, it is relatively inefficient from a network management point of view. Moreover, when the number of mobile terminals requesting ephemeris data increases, the problem of using bandwidth, another scarce resource, is not alleviated. Such might clog the SDCCH channel in a GSM system. It should be appreciated that mobile network 40 and server 202 as fixed installations may continually monitor

the ephemeris information, and always have readily available ephemeris information for downloading to the mobile terminal 100 through the base station 50.

Exemplary methodology of one embodiment of the present invention is illustrated in flow chart form in Figure 5. Initially, almanac information, which may be valid for up to six months or more, is stored in memory 124 of the mobile terminal 100 (block 300). Mobile terminal 100 may periodically receive information about its present coarse location. This information may be broadcast by the mobile network 40, reported to the mobile terminal 100 upon inquiry by the mobile terminal 100, or some other mechanism. For example, this location information may be stored from a previous location determination or the mobile terminal 100 may have a database with cell identification codes correlated to a position.

Upon receipt of a request for location from the application 210 (block 302), the mobile terminal 100 accesses memory 124 and particularly the almanac information stored in memory 124 (block 304). It is possible that the mobile terminal 100 may have ephemeris information stored in memory 124. Should such ephemeris information be available, the mobile terminal 100 may alternatively access the ephemeris information. Mobile terminal 100 then determines which subset of the position detection assisting devices should be visible from the entirety of the position detection system from which to determine location (block 306). This visibility determination can be made because the mobile terminal 100 knows a coarse location and a time. The time may be provided by an internal clock or from the mobile network 40 as needed or desired. Additionally, the mobile terminal 100 may receive doppler and code phase information from the mobile network 40. Armed with the location and time, the mobile terminal 100 may determine which position detection assisting devices are in theory visible to the antenna of the mobile terminal 100. Thus, for example, if only six of the twenty-eight GPS satellites 201 are

above the horizon at this time of the day in this coarse location, only those six would be “visible.” The same is true of base stations 50. Only certain base stations 50 may be “visible” to the mobile terminal 100 depending on coarse location of the mobile terminal 100. Mobile terminal 100 then evaluates the freshness of the information in the almanac or ephemeris that has been accessed (block 308). Evaluating a time stamp and comparing it to a certain threshold may do this. In particular, ephemeris information is typically valid for approximately four hours. Thus, if the time stamp is less than four hours old, the ephemeris may be considered fresh. It is certainly possible to create other tolerances of freshness as needed or desired.

Mobile terminal 100 then requests from either the server 202 or the mobile network 40 contemporary or ephemeris information relating only to those position detection assisting devices that are visible (block 310) as indicated by the earlier determination and that are stale. Note that contemporary information may be requested for all visible devices regardless of freshness. In an alternate embodiment, if more position detection assisting devices are visible than required to make an accurate position determination, then the mobile terminal 100 may further refine the subset to include only a necessary and sufficient number of position detection assisting devices. For example, if seven satellites are visible, and only four are required to determine the location of the mobile terminal 100, then ephemeris is only requested for four of the seven. This further saves bandwidth demands on the mobile network 40.

Mobile terminal 100 then determines its location (block 312) by using the visible position detection assisting devices. Mobile terminal 100 may report its position to the application 210 that originally requested the information (block 314).

Mobile terminal 100 may optionally update information in the almanac stored in memory 124 with the most recently downloaded ephemeris information (block 316). This update may

actually update ephemeris information in the mobile terminal, or be translated to almanac information as suggested in commonly assigned application serial number _____, entitled POSITION DETECTION SYSTEM INTEGRATED INTO MOBILE TERMINAL, concurrently filed, by David McMahon, which is herein incorporated by reference in its entirety. Note that while
5 some events must take place before others, the precise order of events is intended to be exemplary and variations in the order in which the steps are performed still fall within the scope of the present invention.

Note that the ability to request information about position detection assisting devices has been built into the SAMPS (System Assisted Mobile Positioning by Satellite) protocol for
10 TIA/EIA-136 rev. C. This saves traffic on the mobile network 40. Further, if consumers are billed on how much bandwidth or how many packets they receive, the present invention may reduce costs to the consumer by minimizing the amount of information that is requested and received by the mobile terminal 100.

Exemplary methodology of a second embodiment of the present invention is illustrated in
15 flow chart form in Figure 6. Initially, almanac information, which may be valid for up to six months or more, is stored in memory 124 of the mobile terminal 100 (block 400). It may be possible that the mobile terminal 100 has ephemeris information stored in memory 124. Mobile terminal 100 may periodically receive information about its present coarse location. This information may be broadcast by the mobile network 40, reported to the mobile terminal 100
20 upon inquiry by the mobile terminal 100, or some other mechanism. For example, this location information may be stored from a previous location determination or the mobile terminal 100 may have a database with cell identification codes correlated to a position.

Upon receipt of a request for location from the application 210 (block 402), the mobile terminal 100 accesses memory 124 and particularly the almanac or ephemeris information stored in memory 124 (block 404). Mobile terminal 100 then determines which subset of the position detection assisting devices should be visible from the entirety of the position detection system from which to determine location (block 406). This visibility determination can be made because the mobile terminal 100 knows a coarse location and a time. The time may be provided by an internal clock or from the mobile network 40 as needed or desired. Additionally, the mobile network 40 may provide doppler and code phase information as needed or desired. Armed with the location and time, the mobile terminal 100 may determine which position detection assisting devices are in theory visible to the antenna of the mobile terminal 100. Thus, for example, if only six of the twenty-eight GPS satellites 201 are above the horizon at this time of the day in this coarse location, only those six should be “visible.” The same is true of base stations 50. Only certain base stations 50 may be “visible” to the mobile terminal 100 depending on coarse location of the mobile terminal 100.

Mobile terminal 100 may then evaluate which of the theoretically visible position assisting devices are actually visible (block 408). This may be done by receiving signals. Thus, nulls, urban canyons, mountainous regions, or other impediments to reception are evaluated.

Mobile terminal 100 then evaluates the freshness of the information in the almanac or ephemeris that has been accessed (block 410). Evaluating a time stamp and comparing it to a certain threshold may do this. In particular, ephemeris information is typically valid for approximately four hours. Thus, if the time stamp is less than four hours old, the ephemeris may be considered fresh. It is certainly possible to create other tolerances of freshness as needed or desired.

Mobile terminal 100 then requests from either the server 202 or the mobile network 40 contemporary or ephemeris information relating only to those position detection assisting devices that are actually visible (block 412) as indicated by the earlier determination and that are stale. Note that contemporary information may be requested for all visible devices regardless of freshness. In an alternate embodiment, if more position detection assisting devices are visible than required to make an accurate position determination, then the mobile terminal 100 may further refine the subset to include only a necessary and sufficient number of position detection assisting devices. For example, if seven satellites are visible, and only four are required to determine the location of the mobile terminal 100, then ephemeris is only requested for four of the seven. This further saves bandwidth demands on the mobile network 40.

Mobile terminal 100 then determines its location (block 414) by using the visible position detection assisting devices. Mobile terminal 100 may report its position to the application 210 that originally requested the information (block 416).

Mobile terminal 100 may optionally update information in the almanac stored in memory 124 with the most recently downloaded ephemeris information (block 418). This update may actually update ephemeris information in the mobile terminal, or be translated to almanac information as suggested in commonly assigned application serial number _____, entitled POSITION DETECTION SYSTEM INTEGRATED INTO MOBILE TERMINAL, concurrently filed, by David McMahon, previously incorporated. Note that while some events must take place before others, the precise order of events is intended to be exemplary and variations in the order in which the steps are performed still fall within the scope of the present invention.

Note that another variant of the present invention is that the mobile terminal 100 generates the request for the ephemeris midway through the position detection assistance device

signal acquisition process so as to not delay total time for computing the position. The signal strength from the position detection assistance devices may be known even before accurate acquisition of the devices is complete.

The present invention may, of course, be carried out in other specific ways than those herein set forth without departing from the scope and the essential characteristics of the invention. The present embodiments are therefore to be construed in all aspects as illustrative and not restrictive and all changes coming within the meaning and equivalency range of the appended claims are intended to be embraced therein.

5

CLAIMS

What is claimed is:

1. A method of facilitating location detection, comprising:

storing information relating to position detection assisting devices in a mobile terminal;

5 referencing said information to determine a subset of the position detection assisting
devices which are available from which to determine location; and

requesting contemporary information about said subset from a mobile network.

10 2. The method of claim 1 further comprising receiving an inquiry as to the present location of
the mobile terminal.

15 3. The method of claim 2 wherein receiving an inquiry as to the present location of the mobile
terminal originates in the mobile terminal.

20 4. The method of claim 2 wherein receiving an inquiry as to the present location of the mobile
terminal originates in a mobile network associated with the mobile terminal.

5 5. The method of claim 2 wherein receiving an inquiry as to the present location of the mobile
terminal originates in a server communicatively connected to a mobile network associated with
20 the mobile terminal.

6. The method of claim 1 wherein requesting contemporary information about said subset from a
mobile network comprises evaluating a time stamp to determine whether the mobile terminal

already has contemporary information about one or more position detection assisting devices in said subset.

7. The method of claim 6 wherein requesting contemporary information comprises requesting
5 contemporary information about only those in said subset about whom contemporary information is not available in the mobile terminal.

8. The method of claim 6 wherein evaluating a time stamp comprises evaluating a time stamp to determine if said time stamp falls within a predetermined threshold.

10 9. The method of claim 8 wherein evaluating a time stamp to determine if said time stamp falls within a predetermined threshold comprises evaluating if said time stamp is more than four hours old.

15 10. The method of claim 1 wherein requesting contemporary information about said subset from a mobile network comprises requesting contemporary information from a server within the mobile network.

20 11. The method of claim 1 wherein requesting contemporary information about said subset from a mobile network comprises requesting contemporary information from a server communicatively connected to said mobile network.

12. The method of claim 1 further comprising receiving the contemporary information at the mobile terminal and locating said mobile terminal based on information received from said subset of position detection assisting devices.

5 13. The method of claim 12 further comprising reporting the location of the mobile terminal as determined by said locating step.

10 14. The method of claim 1 wherein referencing said information to determine a subset of the position detection assisting devices which are available comprises determining a subset comprising only the position detection assisting devices necessary and sufficient from which to determine location.

15 15. A mobile terminal comprising:
a transceiver; and
a control system operatively connected to said transceiver, wherein said control system stores information relating to a plurality of position detection assisting devices within a position detection system and solicits contemporary information from a mobile network via said transceiver relating to a subset of said position detection assisting devices.

20 16. The mobile terminal of claim 15 wherein said control system determines a present location of the mobile terminal after soliciting said contemporary information.

17. The mobile terminal of claim 15 wherein information relating to a plurality of position detection assisting devices comprises information about a satellite-based position detection system.

5 18. The mobile terminal of claim 17 wherein said information comprises information relating to a plurality of satellites within a GPS.

19. The mobile terminal of claim 15 wherein said information relating to a plurality of position detection assisting devices comprises information about a terrestrial position detection system.

10 20. The mobile terminal of claim 15 wherein said information relating to a plurality of position detection assisting devices comprises information relating to a mixed satellite based and terrestrial position detection system.

15 21. A communication system comprising:

a server comprising contemporary information relating to a position detection system;

a mobile network; and

a mobile terminal communicatively connected to said server through said mobile

network, said mobile terminal storing local information relating to the position detection system

20 and soliciting a subset of said contemporary information from said server based in part on said local information.

22. The communication system of claim 21 wherein said local information comprises an almanac.

23. The communication system of claim 21 wherein said contemporary information comprises
5 satellite ephemeris.

24. The communication system of claim 21 wherein said mobile terminal determines a number of available position detection assisting devices within the position detection system based on a coarse location of the mobile terminal.

10 25. The communication system of claim 21 wherein said server forms a part of said mobile network.

15 26. The communication system of claim 21 wherein said server is communicatively connected to said mobile network.

27. A method of facilitating location detection, comprising:

storing information relating to position detection assisting devices in a mobile terminal;

referencing said information to determine a subset of the position detection assisting devices which are theoretically visible from which to determine location;

5 receiving signals from position detection assisting devices which are actually visible to the mobile terminal; and

requesting contemporary information about the position detection assisting devices which are actually visible from a mobile network.

10 28. A method of facilitating location detection using a satellite based positioning system, comprising:

securing at a mobile terminal, from a mobile network accurate time, doppler, and code phase information for satellites that are theoretically available;

acquiring a signal from one or more of the satellites that are theoretically available; and

15 requesting ephemeris information only for those satellites previously acquired.

29. A method of facilitating location detection using a satellite based positioning system,
comprising:

evaluating an almanac within a mobile terminal to determine which satellites are
theoretically available based on a coarse location and time of the mobile terminal;

5 securing at the mobile terminal, from a mobile network accurate time information for
satellites that are theoretically available;

deriving, at the mobile terminal, doppler and code phase information for the satellites that
are theoretically available;

acquiring a signal from one or more of the satellites that are theoretically available; and

10 requesting ephemeris information only for those satellites previously acquired.

30. The method of claim 29 wherein requesting ephemeris information comprises requesting
ephemeris information for only those satellites whose previously stored ephemeris information is
stale.

15 31. The method of claim 29 wherein acquiring a signal comprises evaluating a signal quality
measurement.

ABSTRACT OF THE DISCLOSURE

A wireless communications mobile terminal conserves bandwidth by determining which position detection assisting devices within a position detection system are available for use and limiting ephemeris information inquiries to only those devices that are available. To make this determination, mobile terminals are provided with an almanac of position information relating to the position detection system. Once the ephemeris information is provided to the mobile terminal, the mobile terminal may determine its location relatively quickly and with a minimal imposition on the mobile network.

5




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG 6

Declaration and Power of Attorney for Patent Application

As below named inventors, we hereby declare that:

Our residences, post office addresses and citizenships are as stated below next to our names,

We believe that we are the original, first and joint inventors of the subject matter which is claimed and for which a patent is sought on the invention entitled **POSITION DETECTION SYSTEM INTEGRATED INTO MOBILE TERMINAL**, the specification of which

☒ is attached hereto.

(Check one)

☐ was filed on _____ as
Application Serial Number _____
and was amended on _____
(if applicable)

We hereby state that we have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

We acknowledge the duty to disclose to the U.S. Patent and Trademark Office all information known to us which is material to patentability (as defined in C.F.R. §1.56) in connection with the examination of this application.

We hereby claim foreign benefits under Title 35, United States Code, §119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

Prior Foreign Application(s)

Priority Claimed

<u>NONE</u> (Number)	_____ (Country)	_____ (Day/Month/Year Filed)	<input type="checkbox"/> YES	<input type="checkbox"/> NO
_____ (Number)	_____ (Country)	_____ (Day/Month/Year Filed)	<input type="checkbox"/> YES	<input type="checkbox"/> NO
_____ (Number)	_____ (Country)	_____ (Day/Month/Year Filed)	<input type="checkbox"/> YES	<input type="checkbox"/> NO

Declaration and Power of Attorney for Patent Application

We hereby claim the benefit under Title 35, United States Code, §120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, §112, we acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, §1.56(a) which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

NONE

(Application Serial No.)

(Filing Date)

(Status: Patented/Pending/Abandoned)

(Application Serial No.)

(Filing Date)

(Status: Patented/Pending/Abandoned)

Power of Attorney: As a named inventor, I hereby appoint the following agents/attorneys to prosecute this application and transact all business in the Patent and Trademark Office connected therewith.

David K. Purks
Registration Number 40,133

Debra K. Stephens
Registration Number 38,211

Kevin A. Sembrat
Registration Number 36,673

Mark C. Terrano
Registration Number 40,200

Stephen A. Calogero
Registration Number 41,491

Kermit D. Lopez
Registration Number 41,953

Dennis J. Williamson
Registration Number 32,338

David R. Irvin
Registration Number 42,682

I. Nelson Wakefield
Registration Number 45,190

Thomas M. Croft
Registration Number 44,051

Gary R. Kuhn
Registration Number 44,198

Declaration and Power of Attorney for Patent Application

And I also hereby appoint the Attorneys and Patent Agents of **Coats & Bennett, P.L.L.C.**, as identified by **Customer Number 24112** in the records of the United States Patent and Trademark Office and as updated from time to time, to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith.



24112

PATENT TRADEMARK OFFICE

Send Correspondence to:

Taylor M. Davenport
Coats & Bennett, P.L.L.C.
P.O. Box 5
Raleigh, North Carolina 27602

Direct Calls to:

Taylor M. Davenport
Telephone: (919) 854-1844
Facsimile: (919) 854-2084

We hereby declare that all statements made herein of our own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

SOLE OR FIRST INVENTOR:

Full name: Leland S. Bloebaum
First Name Middle Name/Initial Last Name
Signature: Leland S Bloebaum Date: 2000 - Sept. - 6
First Name Middle Name Last Name Year-Month-Day


Residence: Cary, North Carolina, USA
City, State, and Country

Citizenship: U.S.

Post Office Address: 103 Battery Point Place, Cary, North Carolina, USA

SECOND INVENTOR, IF ANY:

Full name: Havish Koorapaty
First Name Middle Name/Initial Last Name

Signature:  Date: 2000-09-06
First Name Middle Name Last Name Year-Month-Day

Residence: Cary, North Carolina, USA
City, State, and Country

Citizenship: India

Post Office Address: Horsepond Court, Cary, NC 27513